

View Online at <https://aerobasegroup.com/nsn/3120-00-606-7344>

Thread Class:

3a

Thread Direction:

Left-hand

Shank Style:

Externally threaded

Overall Length:

3.9925 inches

Bore Diameter:

Between 0.7495 inches and 0.7500 inches

Outer Member Outside Diameter:

Between 1.7400 inches and 1.7500 inches

Bore Center To Shank End Distance:

Between 3.1000 inches and 3.1400 inches

Outer Member Width:

Between 0.6820 inches and 0.6920 inches

Inner Member Width:

Between 0.8700 inches and 0.8750 inches

Shank Thread Length:

Between 1.9800 inches and 2.0600 inches

Static Radial Load Rating:

18000 pounds

Thread Diameter:

0.8750 inches

Thready Qty Per Inch (tpi):

14

Hardness Rating:

39.0 rockwell c inner member

Special Features:

Keyway nas 559 on shank 0.1560 min, 0.1610 in. Maximum width

Material:

Steel comp 630 race insert

Material Specification:

Ams5662 assn standard single material response inner member or ams5664 assn standard single material response inner member

Surface Treatment:

Silver outer race member

Surface Treatment Specification:

Ams 2410 assn standard single treatment response outer race member

Style Designator:

Ball type

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0