

View Online at <https://aerobasegroup.com/nsn/3120-00-606-7344>

**Thread Class:**

3a

**Thread Direction:**

Left-hand

**Shank Style:**

Externally threaded

**Overall Length:**

3.9925 inches

**Bore Diameter:**

Between 0.7495 inches and 0.7500 inches

**Outer Member Outside Diameter:**

Between 1.7400 inches and 1.7500 inches

**Bore Center To Shank End Distance:**

Between 3.1000 inches and 3.1400 inches

**Outer Member Width:**

Between 0.6820 inches and 0.6920 inches

**Inner Member Width:**

Between 0.8700 inches and 0.8750 inches

**Shank Thread Length:**

Between 1.9800 inches and 2.0600 inches

**Static Radial Load Rating:**

18000 pounds

**Thread Diameter:**

0.8750 inches

**Thready Qty Per Inch (tpi):**

14

**Hardness Rating:**

39.0 rockwell c inner member

**Special Features:**

Keyway nas 559 on shank 0.1560 min, 0.1610 in. Maximum width

**Material:**

Steel comp 630 race insert

**Material Specification:**

Ams5662 assn standard single material response inner member or ams5664 assn standard single material response inner member

**Surface Treatment:**

Silver outer race member

**Surface Treatment Specification:**

Ams 2410 assn standard single treatment response outer race member

**Style Designator:**

Ball type

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A045a0