

View Online at <https://aerobasegroup.com/nsn/3120-00-612-7490>

Thread Class:

3b

Thread Direction:

Right-hand

Shank Style:

Internally threaded w/bead and wrench flats and inspection hole

Overall Length:

2.8430 inches

Bore Diameter:

Between 0.2495 inches and 0.2515 inches

Outer Member Outside Diameter:

0.9370 inches

Bore Center To Shank End Distance:

Between 2.3650 inches and 2.3850 inches

Outer Member Width:

0.4330 inches

Inner Member Width:

Between 0.5880 inches and 0.5930 inches

Shank Thread Length:

Between 0.7180 inches and 0.8120 inches

Inspection Hole Center To End Distance:

Between 0.4270 inches and 0.4470 inches

Shank Width Across Wrench Flats:

Between 0.4280 inches and 0.4480 inches

Thread Diameter:

0.312 inches

Thready Qty Per Inch (tpi):

24

Hardness Rating:

26.0 rockwell c rod end body and 32.0 rockwell c rod end body

Special Features:

0.2920 in. Max, 0.3200 in. Maximum offset between centerlines of bore and shank

Material:

Steel inner member

Surface Treatment:

Chromium inner member

Style Designator:

Ball type

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A045a0