## NSN 3120-00-661-4135

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-00-661-4135

O۱	erall/	Le	n	g	tŀ	1:	
_		_	_	_	_	_	

Between 0.3020 inches and 0.3170 inches

**Body Outside Diameter:** 

Between 0.3756 inches and 0.3761 inches

**Body Inside Diameter:** 

Between 0.2500 inches and 0.2515 inches

Flange Outside Diameter:

Between 0.4900 inches and 0.5100 inches

Flange Width:

Between 0.0570 inches and 0.0620 inches

**Corner Shape:** 

Undercut left flange body corner

Surface Finish:

100.0 microinches intermediate layer

**Special Features:** 

Id and od to be parallel and concentric within 0.0030 tir

Material:

Steel comp 4130 or steel comp 8630

**Material Specification:** 

Mil-s-6758 military specification 1st material response or mil-s-6050 military specification 2nd material response

**Surface Treatment:** 

Cadmium

**Surface Treatment Specification:** 

Qq-p-416, type 2, cl 3 federal specification single treatment response

Style Designator:

Solid, external flange one end

**Specification Data:** 

80205-nas77 professional/industrial association standard

**Specification Or Standard:** 

1 type and 1 grade

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A045a0

Mil-std (military Standard):

Mil-s-6758 spec.