# NSN 3120-00-661-5040

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-00-661-5040

## **Overall Length:**

Between 0.2320 inches and 0.2470 inches

## **Body Outside Diameter:**

Between 0.3131 inches and 0.3136 inches

## **Body Inside Diameter:**

Between 0.1900 inches and 0.1915 inches

## Flange Outside Diameter:

Between 0.4270 inches and 0.4470 inches

## Flange Width:

Between 0.0570 inches and 0.0620 inches

## Corner Shape:

Undercut left flange body corner

## Surface Finish:

100.0 microinches intermediate layer

## **Special Features:**

Id and od to be parallel and concentric within 0.0030 tir

## Material:

Steel comp 4130 or steel comp 8630

## Material Specification:

Mil-s-6758 military specification 1st material response or mil-s-6050 military specification 2nd material response

## Surface Treatment:

Cadmium

## Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

## Style Designator:

Solid, external flange one end

## **Specification Data:**

80205-nas77 professional/industrial association standard

## Shelf Life:

N/a

## Unit Of Measure:

```
---
```

## Demilitarization:

No

Fiig:

A045a0

Mil-std (military Standard):

Mil-s-6758 spec.