# NSN 3120-00-661-5192

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-00-661-5192

## **Overall Length:**

Between 0.4920 inches and 0.5070 inches

### Body Outside Diameter:

Between 0.4381 inches and 0.4386 inches

## Body Inside Diameter:

Between 0.3125 inches and 0.3140 inches

## Flange Outside Diameter:

Between 0.5520 inches and 0.5720 inches

## Flange Width:

Between 0.0570 inches and 0.0620 inches

## Corner Shape:

Undercut left flange body corner

## Surface Finish:

100.0 microinches intermediate layer

## **Special Features:**

Id and od to be parallel and concentric within 0.0030 tir

#### Material:

Steel comp 4130 or steel comp 8630

#### Material Specification:

Mil-s-6758 military specification 1st material response or mil-s-6050 military specification 2nd material response

### Surface Treatment:

Cadmium and chromate

#### Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

#### Style Designator:

Solid, external flange one end

#### **Specification Data:**

80205-nas77 professional/industrial association standard

#### Shelf Life:

N/a

#### Unit Of Measure:

```
---
```

#### Demilitarization:

No

Fiig:

#### A045a0

Mil-std (military Standard):

Mil-s-6758 spec.