

View Online at <https://aerobasegroup.com/nsn/3120-00-661-7482>

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Shank Style:**

Internally threaded w/hexagon end and inspection hole

**Overall Length:**

Between 1.7400 inches and 1.7600 inches

**Bore Diameter:**

Between 0.1895 inches and 0.1900 inches

**Outer Member Outside Diameter:**

Between 0.7400 inches and 0.7600 inches

**Bore Center To Shank End Distance:**

Between 1.3650 inches and 1.3850 inches

**Outer Member Width:**

Between 0.3230 inches and 0.3330 inches

**Inner Member Width:**

Between 0.4320 inches and 0.4370 inches

**Shank Thread Length:**

Between 0.7188 inches and 0.8125 inches

**Inspection Hole Center To End Distance:**

Between 0.3070 inches and 0.3170 inches

**Shank Width Across Wrench Flats:**

Between 0.4580 inches and 0.4780 inches

**Thread Diameter:**

0.250 inches

**Thready Qty Per Inch (tpi):**

28

**Lubrication Feature:**

Groove external inner member

**Special Features:**

0.0100 in. By 45.0 dea chamfer both ends of bore, 10.0 degrees anfular movment either direction

**Material:**

Steel rod end body

**Material Specification:**

66 federal standard single material response inner member

**Surface Treatment:**

Cadmium rod end body

**Style Designator:**

Ball type

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A045a0