

View Online at <https://aerobasegroup.com/nsn/3120-00-661-7524>

Thread Class:

3b

Thread Direction:

Right-hand

Shank Style:

Internally threaded w/bead and wrench flats and inspection hole

Overall Length:

2.1250 inches

Bore Diameter:

Between 0.3745 inches and 0.3765 inches

Outer Member Outside Diameter:

Between 0.9900 inches and 1.0100 inches

Bore Center To Shank End Distance:

Between 1.6150 inches and 1.6350 inches

Outer Member Width:

0.4110 inches

Inner Member Width:

Between 0.4950 inches and 0.5000 inches

Shank Thread Length:

Between 0.9058 inches and 0.9995 inches

Inspection Hole Center To End Distance:

Between 0.4640 inches and 0.4740 inches

Shank Width Across Wrench Flats:

Between 0.5520 inches and 0.5720 inches

Thread Diameter:

0.375 inches

Features Provided:

Flush lubrication fitting

Thready Qty Per Inch (tpi):

24

Lubrication Feature:

Groove external inner member

Material:

Steel rod end body

Material Specification:

66 federal standard single material response inner member

Style Designator:

Ball type

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A045a0