

View Online at <https://aerobasegroup.com/nsn/3120-00-661-7600>

Thread Class:

3b

Thread Direction:

Left-hand

Shank Style:

Internally threaded w/hexagon end and inspection hole

Overall Length:

Between 2.7710 inches and 2.7910 inches

Bore Diameter:

Between 0.4995 inches and 0.5015 inches

Outer Member Outside Diameter:

Between 1.3020 inches and 1.3220 inches

Bore Center To Shank End Distance:

Between 2.1250 inches and 2.1350 inches

Outer Member Width:

Between 0.4950 inches and 0.5050 inches

Inner Member Width:

Between 0.6200 inches and 0.6250 inches

Shank End To Shoulder Length:

Between 1.1558 inches and 1.2495 inches

Shank Thread Length:

Between 1.1558 inches and 1.2495 inches

Inspection Hole Center To End Distance:

Between 0.5890 inches and 0.5990 inches

Shank Width Across Wrench Flats:

Between 0.8650 inches and 0.8850 inches

Thread Diameter:

0.500 inches

Features Provided:

Flush lubrication fitting

Thready Qty Per Inch (tpi):

20

Lubrication Feature:

Groove internal surfaces

Material:

Steel outer race member

Surface Treatment:

Cadmium

Style Designator:

Ball type extended one side

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0