NSN 3120-00-661-7603

Rod End Plain Bearing - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3120-00-661-7603

| Thread Class: |
|---|
| 3b |
| Thread Direction: |
| Right-hand |
| Shank Style: |
| Internally threaded w/bead and wrench flats and inspection hole |
| Overall Length: |
| Between 1.3650 inches and 1.3850 inches |
| Bore Diameter: |
| Between 0.1895 inches and 0.1915 inches |
| Outer Member Outside Diameter: |
| Between 0.6150 inches and 0.6350 inches |
| Bore Center To Shank End Distance: |
| Between 1.0520 inches and 1.0720 inches |
| Outer Member Width: |
| Between 0.2450 inches and 0.2550 inches |
| Inner Member Width: |
| Between 0.3070 inches and 0.3120 inches |
| Shank Thread Length: |
| Between 0.5308 inches and 0.6245 inches |
| Inspection Hole Center To End Distance: |
| Between 0.3070 inches and 0.3120 inches |
| Shank Width Across Wrench Flats: |
| Between 0.3070 inches and 0.3120 inches |
| Thread Diameter: |
| 0.190 inches |
| Features Provided: |
| Flush lubrication fitting |
| Thready Qty Per Inch (tpi): |
| 32 |
| Material: |
| Steel rod end body |
| Material Specification: |
| 66 federal standard single material response inner member |
| Style Designator: |
| Ball type |
| Thread Series Designator: |
| Unf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| |

NSN 3120-00-661-7603

Rod End Plain Bearing - Page 2 of 2

Demilitarization:

No

Fiig:

A045a0

