# NSN 3120-00-661-7976

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-00-661-7976

## **Overall Length:**

Between 0.4320 inches and 0.4470 inches

### **Body Outside Diameter:**

Between 0.6257 inches and 0.6265 inches

# Body Inside Diameter:

Between 0.5000 inches and 0.5015 inches

## Flange Outside Diameter:

Between 0.7400 inches and 0.7600 inches

### Flange Width:

Between 0.0570 inches and 0.0620 inches

## Corner Shape:

Undercut left flange body corner

## Surface Finish:

100.0 microinches intermediate layer

## **Special Features:**

Id and od to be parallel and concentric within 0.0030 tir

# Material:

Steel comp 4130 or steel comp 8630

## Material Specification:

Mil-s-6758 military specification 1st material response or mil-s-6050 military specification 2nd material response

# Surface Treatment:

Cadmium

# Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

## Style Designator:

Solid, external flange one end

### **Specification Data:**

80205-nas77 professional/industrial association standard

### Shelf Life:

N/a

# Unit Of Measure:

```
--
```

# Demilitarization:

No

Fiig:

A045a0

Mil-std (military Standard):

Mil-s-6758 spec.