# NSN 3120-00-662-0009

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-00-662-0009

## **Overall Length:**

Between 0.1770 inches and 0.1920 inches

#### Body Outside Diameter:

Between 0.3760 inches and 0.3765 inches

## Body Inside Diameter:

Between 0.2495 inches and 0.2505 inches

#### Flange Outside Diameter:

Between 0.4900 inches and 0.5100 inches

## Flange Width:

Between 0.0570 inches and 0.0620 inches

## Corner Shape:

Square outside right corner

## Material:

Steel comp 4130 or steel comp 4135

## Material Specification:

Mil-t-6736, cond n military specification 1st material response or ams 6372 assn standard 2nd material response

# Surface Treatment:

Cadmium right end surface of left flange

# Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response right end surface of left flange

# Style Designator:

Solid, external flange one end

# Test Data Document:

81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### Shelf Life:

N/a

Unit Of Measure:

```
---
```

# Demilitarization:

No

Fiig:

A045a0

Mil-std (military Standard):

Mil-t-6736 spec.