

View Online at <https://aerobasegroup.com/nsn/3120-00-662-4002>

Thread Class:

3a

Thread Direction:

Right-hand

Shank Style:

Externally threaded

Overall Length:

Between 2.7500 inches and 2.7800 inches

Bore Diameter:

Between 0.2495 inches and 0.2500 inches

Lubrication Material:

Grease

Outer Member Outside Diameter:

1.0000 inches

Bore Center To Shank End Distance:

2.2500 inches

Outer Member Width:

Between 0.2810 inches and 0.3010 inches

Inner Member Width:

Between 0.3700 inches and 0.3750 inches

Shank Thread Length:

1.1000 inches

Static Radial Load Rating:

5246 pounds

Thread Diameter:

0.375 inches

Features Provided:

External lubrication fitting

Thready Qty Per Inch (tpi):

24

Hardness Rating:

32.2 rockwell c rod end body and 38.8 rockwell c rod end body

Lubrication Feature:

Groove external inner member

Material:

Steel comp e52100 inner member

Material Specification:

Mil-s-7420 federal specification single material response inner member

Surface Treatment:

Cadmium rod end body

Surface Treatment Specification:

Qq-c-320, cl 2 federal specification single treatment response inner member

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0

Mil-std (military Standard):

Mil-s-5000 spec.