

View Online at <https://aerobasegroup.com/nsn/3120-00-662-8049>

Thread Class:

3b

Thread Direction:

Right-hand

Shank Style:

Internally threaded w/bead and wrench flats and inspection hole

Overall Length:

Between 2.3650 inches and 2.3850 inches

Bore Diameter:

Between 0.2495 inches and 0.2515 inches

Outer Member Outside Diameter:

Between 1.1150 inches and 1.1350 inches

Bore Center To Shank End Distance:

Between 1.8020 inches and 1.8220 inches

Outer Member Width:

Between 0.4320 inches and 0.4420 inches

Inner Member Width:

Between 0.6820 inches and 0.6870 inches

Shank Thread Length:

1.0620 inches

Inspection Hole Center To End Distance:

Between 0.5260 inches and 0.5360 inches

Shank Width Across Wrench Flats:

Between 0.6150 inches and 0.6350 inches

Static Radial Load Rating:

5356 pounds

Thread Diameter:

0.438 inches

Features Provided:

External lubrication fitting

Thready Qty Per Inch (tpi):

20

Hardness Rating:

60.0 rockwell c inner member

Lubrication Feature:

Groove race insert

Special Features:

Magnetic particle inspection required

Material:

Steel rod end body

Surface Treatment:

Cadmium rod end body

Style Designator:

Ball type

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0