

View Online at <https://aerobasegroup.com/nsn/3120-00-662-9321>

**Thread Class:**

3a

**Thread Direction:**

Left-hand

**Shank Style:**

Externally threaded

**Overall Length:**

Between 1.4270 inches and 1.4470 inches

**Bore Diameter:**

Between 0.1895 inches and 0.1915 inches

**Outer Member Outside Diameter:**

Between 0.7400 inches and 0.7600 inches

**Bore Center To Shank End Distance:**

Between 1.0520 inches and 1.0720 inches

**Outer Member Width:**

Between 0.3230 inches and 0.3330 inches

**Inner Member Width:**

Between 0.4320 inches and 0.4370 inches

**Shank Thread Length:**

Between 0.4060 inches and 0.4990 inches

**Static Radial Load Rating:**

2848 pounds

**Thread Diameter:**

0.250 inches

**Thready Qty Per Inch (tpi):**

28

**Lubrication Feature:**

Groove internal inner member

**Material:**

Steel rod end body

**Material Specification:**

66 federal standard single material response inner member

**Surface Treatment:**

Cadmium rod end body

**Style Designator:**

Ball type

**Thread Series Designator:**

Unf

**Reference Number Differentiating Characteristics:**

As differentiated by letter m on shank for aircraft use

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A045a0