## NSN 3120-00-670-5327

Sleeve Bushing - Page 1 of 1

Mil-std (military Standard):

Mil-s-6049 spec.



View Online at https://aerobasegroup.com/nsn/3120-00-670-5327

Overall Length:
Between 1.5595 inches and 1.5655 inches
Body Outside Diameter:
Between 0.3760 inches and 0.3765 inches
Body Inside Diameter:
Between 0.2339 inches and 0.2349 inches
Flange Outside Diameter:
Between 0.4900 inches and 0.5100 inches
Flange Width:
Between 0.0615 inches and 0.0625 inches
Corner Shape:
Undercut left flange body corner
Hardness Rating:
26.0 rockwell c and 33.0 rockwell c
Material:
Steel comp 8740 or steel comp 8630 or steel comp 4130 or steel comp 4140
Material Specification:
66 federal standard 1st material response or mil-s-6049 military specification 1st material response or 66 federal standard 2nd material
response or mil-s-6050 military specification 2nd material response or mil-t-6732 military specification 2nd material response or 66 federal
standard 3rd material response or mil-s-6758 military specification 3rd material response or mil-t-6736 military specification 3rd material
response or mil-s-5626 military specification 4th material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416, type 2, cl 2 federal specification single treatment response
Style Designator:
Solid, external flange one end
Specification Data:
97499-22-003 through 22-024 manufacturers specification
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A045a0