NSN 3120-00-671-6011

Sleeve Bushing - Page 1 of 1

AeroBase Group

View Online at https://aerobasegroup.com/nsn/3120-00-671-6011

| Hole Diameter: |
|--|
| 0.1250 inches first |
| Overall Length: |
| Between 0.4900 inches and 0.5100 inches |
| Body Outside Diameter: |
| Between 1.2505 inches and 1.2510 inches |
| Body Inside Diameter: |
| Between 0.9890 inches and 0.9930 inches |
| Flange Outside Diameter: |
| Between 1.4900 inches and 1.5100 inches |
| Flange Width: |
| Between 0.0550 inches and 0.0650 inches |
| Lubricant Accommodation Style: |
| Grooved circular |
| Corner Shape: |
| Square outside right corner |
| Surface Finish: |
| 125.0 microinches intermediate layer |
| Antirotation/lubrication Type And Quantity: |
| 2 hole |
| Surface Groove Location And Quantity: |
| 1 external |
| Special Features: |
| Two holes through wall at centrally located groove |
| Material: |
| Steel comp 4130 |
| Material Specification: |
| Mil-s-6758 military specification single material response |
| Style Designator: |
| Solid, external flange one end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A045a0 |
| Mil-std (military Standard): |
| Mil-s-6758 spec. |
| |