NSN 3120-00-683-9431

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-00-683-9431

Over	all I	en	ath:
~~~	an L	-611	иит.

Between 0.3200 inches and 0.3700 inches

### **Body Outside Diameter:**

Between 0.6257 inches and 0.6265 inches

# **Body Inside Diameter:**

Between 0.4840 inches and 0.4910 inches

#### Flange Outside Diameter:

Between 0.7400 inches and 0.7600 inches

#### Flange Width:

Between 0.0550 inches and 0.0600 inches

#### **Corner Shape:**

Undercut left flange body corner

#### **Special Features:**

Id and od to be parallel and concentric within 0.0030 tir

#### Material:

Steel comp 4130 or steel comp 8630

# **Material Specification:**

Mil-s-6758 military specification 1st material response or mil-s-6050 military specification 2nd material response

#### **Surface Treatment:**

Cadmium

# **Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

#### **Style Designator:**

Solid, external flange one end

# **Specification Data:**

80205-nas538 professional/industrial association standard

# Shelf Life:

N/a

# **Unit Of Measure:**

# **Demilitarization:**

No Fiig:

A045a0

# Mil-std (military Standard):

Mil-s-6758 spec.