NSN 3120-00-684-2386

Rod End Plain Bearing - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3120-00-684-2386

| Thread Class: |
|---|
| 3b |
| Thread Direction: |
| Right-hand |
| Shank Style: |
| Internally threaded w/bead and wrench flats and inspection hole |
| Overall Length: |
| 2.7810 inches |
| Bore Diameter: |
| Between 0.4995 inches and 0.5015 inches |
| Outer Member Outside Diameter: |
| 1.3120 inches |
| Bore Center To Shank End Distance: |
| 2.1250 inches |
| Outer Member Width: |
| 0.5050 inches |
| Inner Member Width: |
| Between 0.6200 inches and 0.6250 inches |
| Shank Thread Length: |
| 1.1870 inches |
| Inspection Hole Center To End Distance: |
| 0.5940 inches |
| Shank Width Across Wrench Flats: |
| 0.7500 inches |
| Thread Diameter: |
| 0.500 inches |
| Features Provided: |
| External lubrication fitting |
| Thready Qty Per Inch (tpi): |
| 20 |
| Lubrication Feature: |
| Groove external inner member |
| Material: |
| Steel rod end body |
| Surface Treatment: |
| Cadmium rod end body |
| Style Designator: |
| Ball type |
| Thread Series Designator: |
| Unf |
| Shelf Life: |
| N/a |
| 190 |

NSN 3120-00-684-2386

Rod End Plain Bearing - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A045a0

