NSN 3120-00-684-2513

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-00-684-2513

O,	/era	ш	l ۵n	ath	٠.
U١	/eia		Len	uu	ı.

Between 0.8830 inches and 0.9030 inches

Body Outside Diameter:

Between 0.3760 inches and 0.3765 inches

Body Inside Diameter:

Between 0.3060 inches and 0.3080 inches

Flange Outside Diameter:

Between 0.4500 inches and 0.4700 inches

Flange Width:

Between 0.2030 inches and 0.2230 inches

Left Internal Flange Hole Diameter:

Between 0.1890 inches and 0.1910 inches

Right Internal Flange Hole Diameter:

Between 0.1890 inches and 0.1910 inches

Left Internal Flange Width:

Between 0.0475 inches and 0.0675 inches

Right Internal Flange Width:

Between 0.7300 inches and 0.7500 inches

Corner Shape:

Square outside right corner

Surface Finish:

125.0 microinches intermediate layer

Material:

Steel comp 1144

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Style Designator:

Solid, external flange one end, internal flange at both ends

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A045a0