

View Online at <https://aerobasegroup.com/nsn/3120-00-689-7207>

Thread Class:

3b

Thread Direction:

Right-hand

Shank Style:

Internally threaded w/bead and wrench flats and inspection hole

Overall Length:

2.3120 inches

Bore Diameter:

Between 0.3745 inches and 0.3750 inches

Outer Member Outside Diameter:

Between 0.9900 inches and 1.0100 inches

Bore Center To Shank End Distance:

Between 1.8020 inches and 1.8220 inches

Outer Member Width:

Between 0.4110 inches and 0.4210 inches

Inner Member Width:

Between 0.4950 inches and 0.5000 inches

Shank Thread Length:

0.9375 inches

Inspection Hole Center To End Distance:

0.4400 inches

Shank Width Across Wrench Flats:

0.5620 inches

Static Radial Load Rating:

8650 pounds

Thread Diameter:

0.375 inches

Thready Qty Per Inch (tpi):

24

Special Features:

Dynamic radial load rating 5125 lbs, thrust limit load rating 2000 lbs, no load rotational starting torque 1 lb 8.0000 in.

Material:

Steel comp 410 race insert

Surface Treatment:

Cadmium rod end body

Style Designator:

Ball type

Test Data Document:

81349-mil-i-6866 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Or 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0