NSN 3120-00-692-9286

Sleeve Bearing - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3120-00-692-9286

II. I. Biranta
Hole Diameter:
0.4375 inches first
Slot Width:
0.6250 inches first and 0.6270 inches first
Slot Length:
0.6250 inches first
Overall Length:
3.7500 inches
Body Outside Diameter:
Between 6.4980 inches and 6.5000 inches
Body Inside Diameter:
Between 5.5055 inches and 5.5075 inches
Flange Outside Diameter:
Between 7.2480 inches and 7.7250 inches
Flange Width:
Between 1.4940 inches and 1.4990 inches
Lubricant Accommodation Style:
Grooved circular
Corner Shape:
Square all corners
Hardness Rating:
58.0 rockwell c
Surface Finish:
125.0 microinches
Antirotation/lubrication Type And Quantity:
4 hole and 4 slot
Surface Groove Location And Quantity:
3 internal
Material:
Silica
Material Specification:
Mil-b-5687, type 2 federal specification all material responses
Surface Treatment:
Phosphate manganese
Surface Treatment Specification:
Mil-p-16232, type m, class 2 federal specification all treatment responses
Style Designator:
Solid, external flange one end
Shelf Life:
N/a
Unit Of Measure:

--

NSN 3120-00-692-9286

Sleeve Bearing - Page 2 of 2



Demilitarization:

No

Fiig:

A045a0

Mil-std (military Standard):

Mil-b-5687 spec.