

View Online at <https://aerobasegroup.com/nsn/3120-00-708-7766>

**Thread Class:**

2b

**Thread Direction:**

Left-hand

**Shank Style:**

Internally threaded w/bead and wrench flats and inspection hole

**Overall Length:**

2.7812 inches

**Bore Diameter:**

Between 0.4995 inches and 0.5015 inches

**Outer Member Outside Diameter:**

Between 1.3025 inches and 1.3225 inches

**Bore Center To Shank End Distance:**

Between 2.1100 inches and 2.1400 inches

**Outer Member Width:**

Between 0.4950 inches and 0.5050 inches

**Inner Member Width:**

Between 0.6200 inches and 0.6250 inches

**Shank Thread Length:**

1.1875 inches

**Inspection Hole Center To End Distance:**

0.5940 inches

**Shank Width Across Wrench Flats:**

0.7500 inches

**Static Radial Load Rating:**

6350 pounds

**Thread Diameter:**

0.500 inches

**Thready Qty Per Inch (tpi):**

20

**Lubrication Feature:**

Groove external inner member

**Special Features:**

Requires magnetic inspection

**Material:**

Steel rod end body

**Surface Treatment:**

Cadmium rod end body

**Style Designator:**

Ball type

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A045a0