NSN 3120-00-738-5890

Sleeve Bearing - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3120-00-738-5890

Hole) Dia	me	ter:
------	-------	----	------

0.0458 inches first and 0.0508 inches first

Overall Length:

Between 0.4900 inches and 0.5100 inches

Body Outside Diameter:

Between 0.4986 inches and 0.4991 inches

Body Inside Diameter:

0.3755 inches

Flange Outside Diameter:

Between 0.7400 inches and 0.7600 inches

Flange Width:

Between 0.0380 inches and 0.0400 inches

Lubricant Accommodation Style:

Grooved circular

Corner Shape:

Square outside right corner

Surface Finish:

16.0 microinches outside diameter surface of body

Antirotation/lubrication Type And Quantity:

4 hole

Surface Groove Location And Quantity:

1 external

Material:

Steel comp 4130

Material Specification:

Mil-s-6758 military specification single material response

Surface Treatment:

Cadmium right end surface of left flange

Surface Treatment Specification:

Qq-p-416 federal specification 1st treatment response right end surface of body

Style Designator:

Solid, external flange one end

Test Data Document:

81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

_

Demilitarization:

No

Fiig:

A045a0

NSN 3120-00-738-5890

Sleeve Bearing - Page 2 of 2



Mil-std (military Standard):

Mil-s-6758 spec.