

View Online at <https://aerobasegroup.com/nsn/3120-00-761-5588>

Thread Class:

3b

Thread Direction:

Right-hand

Shank Style:

Internally threaded w/bead and wrench flats and inspection hole

Overall Length:

Between 1.8650 inches and 1.8875 inches

Bore Diameter:

Between 0.3120 inches and 0.3125 inches

Outer Member Outside Diameter:

Between 1.0000 inches and 1.0005 inches

Bore Center To Shank End Distance:

Between 1.3650 inches and 1.3850 inches

Outer Member Width:

Between 0.3810 inches and 0.3910 inches

Inner Member Width:

Between 0.5400 inches and 0.5450 inches

Shank Thread Length:

Between 0.7200 inches and 0.7800 inches

Inspection Hole Center To End Distance:

Between 0.3650 inches and 0.3850 inches

Shank Width Across Wrench Flats:

Between 0.4950 inches and 0.5000 inches

Thread Diameter:

0.313 inches

Thready Qty Per Inch (tpi):

24

Material:

Stainless steel rod end body

Surface Treatment:

Cadmium rod end body

Surface Treatment Specification:

Qq-p-416, type 1, cl 2 federal specification single treatment response rod end body

Style Designator:

Ball type

Test Data Document:

81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A045a0