

View Online at <https://aerobasegroup.com/nsn/3120-00-781-4737>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Shank Style:**

Externally threaded

**Overall Length:**

Between 2.8595 inches and 2.8895 inches

**Bore Diameter:**

Between 0.3745 inches and 0.3750 inches

**Outer Member Outside Diameter:**

Between 1.1150 inches and 1.1350 inches

**Bore Center To Shank End Distance:**

Between 2.3020 inches and 2.3220 inches

**Outer Member Width:**

Between 0.3700 inches and 0.3800 inches

**Inner Member Width:**

Between 0.4950 inches and 0.5000 inches

**Shank Thread Length:**

Between 1.3440 inches and 1.4380 inches

**Static Radial Load Rating:**

10140 pounds

**Thread Diameter:**

0.438 inches

**Thready Qty Per Inch (tpi):**

20

**Hardness Rating:**

55.0 rockwell c inner member and 62.0 rockwell c inner member

**Special Features:**

Keyway in shank

**Material:**

Steel comp 630 rod end body

**Surface Treatment:**

Chromium inner member

**Style Designator:**

Ball type

**Test Data Document:**

81349-mil-i-6866 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A045a0