

View Online at <https://aerobasegroup.com/nsn/3120-00-787-9825>

**Thread Class:**

3b

**Thread Direction:**

Right-hand

**Shank Style:**

Internally threaded w/inspection hole

**Overall Length:**

Between 2.4720 inches and 2.4920 inches

**Bore Diameter:**

Between 0.1860 inches and 0.1870 inches

**Outer Member Outside Diameter:**

Between 0.6150 inches and 0.6350 inches

**Bore Center To Shank End Distance:**

Between 2.1600 inches and 2.1800 inches

**Outer Member Width:**

Between 0.2200 inches and 0.2300 inches

**Inner Member Width:**

Between 0.3070 inches and 0.3120 inches

**Shank Thread Length:**

0.6600 inches

**Inspection Hole Center To End Distance:**

Between 0.3020 inches and 0.3220 inches

**Static Radial Load Rating:**

800 pounds

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Hardness Rating:**

60.0 rockwell c inner member

**Special Features:**

0.2500 in. Min., 0.3000 in. Maximum w by 0.0620 min., 0.0720 in. Max. Depth of slot on two sides of shank, 0.8550 in. Min., 0.8750 in. Max.

Lg froncenter of bore

**Style Designator:**

Ball type

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A045a0