

View Online at <https://aerobasegroup.com/nsn/3120-00-807-4283>

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Shank Style:**

Internally threaded w/bead and wrench flats and inspection hole

**Overall Length:**

2.3750 inches

**Bore Diameter:**

Between 0.4375 inches and 0.4390 inches

**Outer Member Outside Diameter:**

Between 1.1150 inches and 1.1350 inches

**Bore Center To Shank End Distance:**

Between 1.7970 inches and 1.8270 inches

**Outer Member Width:**

Between 0.4320 inches and 0.4420 inches

**Inner Member Width:**

Between 0.5570 inches and 0.5620 inches

**Shank Thread Length:**

Between 1.0312 inches and 1.1250 inches

**Inspection Hole Center To End Distance:**

Between 0.5210 inches and 0.5410 inches

**Shank Width Across Wrench Flats:**

Between 0.6100 inches and 0.6400 inches

**Static Radial Load Rating:**

4300 pounds

**Thread Diameter:**

0.438 inches

**Thready Qty Per Inch (tpi):**

20

**Lubrication Feature:**

Groove race insert

**Material:**

Steel rod end body

**Surface Treatment:**

Cadmium rod end body

**Style Designator:**

Ball type

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A045a0