# NSN 3120-00-812-1763

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-00-812-1763

#### **Overall Length:**

Between 0.2300 inches and 0.2400 inches

#### **Body Outside Diameter:**

Between 0.5006 inches and 0.5013 inches

## **Body Inside Diameter:**

Between 0.3590 inches and 0.3660 inches

#### Flange Outside Diameter:

Between 0.6150 inches and 0.6350 inches

#### Flange Width:

Between 0.0550 inches and 0.0600 inches

# Corner Shape:

Undercut left flange body corner

# Special Features:

Id and od to be parallel and concentric within 0.0030 tir

# Material:

Steel comp 4130 or steel comp 8630

# **Material Specification:**

Mil-s-6758 military specification 1st material response or mil-s-6050 military specification 2nd material response

#### Surface Treatment:

Cadmium

# Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

## Style Designator:

22c solid, external flange one end

#### **Specification Data:**

80205-nas538 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

# Demilitarization:

No

Fiig:

A045a0

# Mil-std (military Standard):

Mil-s-6758 spec.