NSN 3120-00-812-1770

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-00-812-1770

Overal	llen	ath.
Overai	IFCI	ıuıı.

Between 0.2600 inches and 0.2700 inches

Body Outside Diameter:

Between 0.4381 inches and 0.4386 inches

Body Inside Diameter:

Between 0.3010 inches and 0.3060 inches

Flange Outside Diameter:

Between 0.5520 inches and 0.5720 inches

Flange Width:

Between 0.0550 inches and 0.0600 inches

Corner Shape:

Undercut left flange body corner

Special Features:

Id and od to be parallel and concentric within 0.0030 tir

Material:

Steel comp 4130 or steel comp 8630

Material Specification:

Mil-s-6758 military specification 1st material response or mil-s-6050 military specification 2nd material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Style Designator:

22c solid, external flange one end

Specification Data:

80205-nas538 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A045a0

Mil-std (military Standard):

Mil-s-6758 spec.