# NSN 3120-00-816-2506

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-00-816-2506

# **Overall Length:**

Between 0.3200 inches and 0.3300 inches

#### Body Outside Diameter:

Between 0.5631 inches and 0.5638 inches

# Body Inside Diameter:

Between 0.4220 inches and 0.4290 inches

#### Flange Outside Diameter:

Between 0.6770 inches and 0.6970 inches

## Flange Width:

Between 0.0550 inches and 0.0600 inches

## Corner Shape:

Undercut left flange body corner

## Special Features:

Id and od to be parallel and concentric within 0.0030 tir

## Material:

Steel comp 4130 or steel comp 8630

# Material Specification:

Mil-s-6758 military specification 1st material response or mil-s-6050 military specification 2nd material response

## Surface Treatment:

Cadmium

#### Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

#### Style Designator:

22c solid, external flange one end

#### **Specification Data:**

80205-nas538 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

#### Demilitarization:

No

Fiig:

A045a0

#### Mil-std (military Standard):

Mil-s-6758 spec.