

View Online at <https://aerobasegroup.com/nsn/3120-00-818-8888>

Thread Class:

3b

Thread Direction:

Right-hand

Shank Style:

Internally threaded w/hexagon end and inspection hole

Overall Length:

Between 1.6770 inches and 1.6970 inches

Bore Diameter:

Between 0.2495 inches and 0.2515 inches

Lubrication Material:

Grease, mil-g-23827

Outer Member Outside Diameter:

Between 0.7400 inches and 0.7600 inches

Bore Center To Shank End Distance:

Between 1.3020 inches and 1.3220 inches

Outer Member Width:

Between 0.2760 inches and 0.2860 inches

Inner Member Width:

Between 0.3700 inches and 0.3750 inches

Shank Thread Length:

0.8120 inches

Inspection Hole Center To End Distance:

Between 0.3070 inches and 0.3170 inches

Shank Width Across Wrench Flats:

0.4680 inches

Static Radial Load Rating:

5390 pounds

Thread Diameter:

0.250 inches

Features Provided:

Flush lubrication fitting and screw plug closure fitting

Thready Qty Per Inch (tpi):

28

Hardness Rating:

59.0 rockwell c inner member and 63.0 rockwell c inner member

Lubrication Feature:

Groove external inner member

Material:

Steel comp e52100 inner member

Surface Treatment:

Cadmium rod end body

Style Designator:

Ball type

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0