

View Online at <https://aerobasegroup.com/nsn/3120-00-818-8888>

**Thread Class:**

3b

**Thread Direction:**

Right-hand

**Shank Style:**

Internally threaded w/hexagon end and inspection hole

**Overall Length:**

Between 1.6770 inches and 1.6970 inches

**Bore Diameter:**

Between 0.2495 inches and 0.2515 inches

**Lubrication Material:**

Grease, mil-g-23827

**Outer Member Outside Diameter:**

Between 0.7400 inches and 0.7600 inches

**Bore Center To Shank End Distance:**

Between 1.3020 inches and 1.3220 inches

**Outer Member Width:**

Between 0.2760 inches and 0.2860 inches

**Inner Member Width:**

Between 0.3700 inches and 0.3750 inches

**Shank Thread Length:**

0.8120 inches

**Inspection Hole Center To End Distance:**

Between 0.3070 inches and 0.3170 inches

**Shank Width Across Wrench Flats:**

0.4680 inches

**Static Radial Load Rating:**

5390 pounds

**Thread Diameter:**

0.250 inches

**Features Provided:**

Flush lubrication fitting and screw plug closure fitting

**Thready Qty Per Inch (tpi):**

28

**Hardness Rating:**

59.0 rockwell c inner member and 63.0 rockwell c inner member

**Lubrication Feature:**

Groove external inner member

**Material:**

Steel comp e52100 inner member

**Surface Treatment:**

Cadmium rod end body

**Style Designator:**

Ball type

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A045a0