# NSN 3120-00-826-8234

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-00-826-8234

Overall	Length:
---------	---------

Between 0.3100 inches and 0.3200 inches

### **Body Outside Diameter:**

Between 0.5006 inches and 0.5013 inches

### **Body Inside Diameter:**

Between 0.3590 inches and 0.3660 inches

### Flange Outside Diameter:

Between 0.6150 inches and 0.6350 inches

### Flange Width:

Between 0.0550 inches and 0.0600 inches

#### **Corner Shape:**

Undercut left flange body corner

### Surface Finish:

63.0 microinches outside diameter surface of body

#### **Special Features:**

Id and od to be parallel and concentric within 0.0030 tir

#### Material:

Steel comp 4130 or steel comp 8630

### **Material Specification:**

Mil-s-6798 military specification 1st material response or mil-s-6050 military specification 2nd material response

### **Surface Treatment:**

Cadmium

### **Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

### Style Designator:

22c solid, external flange one end

## **Specification Data:**

80205-nas538 professional/industrial association standard

### Shelf Life:

N/a

### **Unit Of Measure:**

--

### Demilitarization:

No

# Fiig:

A045a0

# Mil-std (military Standard):

Mil-s-6798 spec.