

View Online at <https://aerobasegroup.com/nsn/3120-00-832-4152>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Shank Style:**

Internally threaded w/bead and wrench flats and inspection hole

**Overall Length:**

Between 2.0475 inches and 2.0620 inches

**Bore Diameter:**

Between 0.1895 inches and 0.1915 inches

**Outer Member Outside Diameter:**

Between 0.8650 inches and 0.8750 inches

**Bore Center To Shank End Distance:**

Between 1.6150 inches and 1.6250 inches

**Outer Member Width:**

0.3320 inches

**Inner Member Width:**

Between 0.4950 inches and 0.5000 inches

**Shank Thread Length:**

0.7500 inches

**Inspection Hole Center To End Distance:**

0.3750 inches

**Shank Width Across Wrench Flats:**

0.5000 inches

**Thread Diameter:**

0.312 inches

**Features Provided:**

Flush lubrication fitting

**Thready Qty Per Inch (tpi):**

24

**Material:**

Steel comp e52100 inner member

**Material Specification:**

66 federal standard single material response inner member

**Surface Treatment:**

Cadmium rod end body

**Style Designator:**

Ball type

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A045a0