## NSN 3120-00-836-2586

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-00-836-2586

| View Online at https://aerobasegroup.com/nsn/3120-00-836-2586  |
|--|
| Overall Length:  |
| Between 0.4325 inches and 0.4375 inches  |
| Body Outside Diameter:   |
| Between 0.6257 inches and 0.6265 inches  |
| Body Inside Diameter:  |
| Between 0.5000 inches and 0.5015 inches  |
| Corner Shape:  |
| Square outside right corner  |
| Surface Finish:  |
| 125.0 microinches intermediate layer   |
| Material:  |
| Steel comp 8630 or steel comp 4130   |
| Material Specification:  |
| Mil-s-6050 military specification 1st material response or mil-s-6758 military specification 2nd material response |
| Surface Treatment:   |
| Cadmium  |
| Surface Treatment Specification:   |
| Qq-p-416, type 2, cl 2 federal specification single treatment response   |
| Style Designator:  |
| 17c solid, plain, no outside flanges   |
| Specification Data:  |
| 80205-nas75 professional/industrial association standard   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A045a0   |
| Mil-std (military Standard):   |
| Mil-s-6050 spec.   |