

View Online at <https://aerobasegroup.com/nsn/3120-00-867-8750>

Hole Diameter:

0.2400 inches and 0.2600 inches first

Overall Length:

Between 1.1905 inches and 1.1925 inches

Body Outside Diameter:

Between 1.7545 inches and 1.7560 inches

Body Inside Diameter:

Between 1.6275 inches and 1.6282 inches

Lubrication Material:

Lubricating oil

End Application:

28058725972

Left Flange Outside Diameter:

Between 2.3140 inches and 2.3740 inches

Right Flange Outside Diameter:

Between 2.3140 inches and 2.3740 inches

Left Flange Width:

Between 0.0810 inches and 0.0830 inches

Right Flange Width:

Between 0.0810 inches and 0.0830 inches

Lubricant Accommodation Style:

Grooved circular

Locking Lug Height:

Between 0.0450 inches and 0.0550 inches

Locking Lug Length:

Between 0.1900 inches and 0.2200 inches

Locking Lug Width:

Between 0.1750 inches and 0.1800 inches

Corner Shape:

Square right flange outside left corner

Antirootation/lubrication Type And Quantity:

1 hole

Hole Spacing Angle:

28.0 degrees

Surface Groove Location And Quantity:

1 internal

Distance From Lug End To End Of Bearing:

Between 0.3535 inches and 0.3630 inches

Material:

Steel outer layer

Material Specification:

Ms13826-1, 96906 mfr ref 1st material response inner layer

Surface Treatment:

Tin

Surface Treatment Specification:

Ms13826-1, 96906 mfr ref single treatment response

Style Designator:

18d half sleeve, external flanges both ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A045a0