NSN 3120-00-867-9003

Sleeve Bushing - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3120-00-867-9003

Hole Diameter: 0.0781 inches first **Slot Width:** 0.2400 inches first and 0.2600 inches first Slot Length: 0.3900 inches first and 0.4100 inches first **Overall Length:** Between 1.1200 inches and 1.1400 inches **Body Outside Diameter:** Between 1.3400 inches and 1.3600 inches **Body Inside Diameter:** Between 1.2510 inches and 1.2520 inches Flange Outside Diameter: Between 1.4900 inches and 1.5100 inches Flange Width: Between 0.2400 inches and 0.2600 inches **Lubricant Accommodation Style:** Grooved circular **Corner Shape:** Square outside right corner **Surface Finish:** 32.0 microinches inside diameter surface of body **Antirotation/lubrication Type And Quantity:** 1 hole and 1 slot **Surface Groove Location And Quantity:** 1 external **Special Features:** Groove located on flange Material: Aluminum alloy **Material Specification:** Qq-a-266 federal specification single material response or qq-a-268 federal specification single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625, type 1 military specification single treatment response **Style Designator:** 22c solid, external flange one end

N/a

Unit Of Measure:

Shelf Life:

NSN 3120-00-867-9003

Sleeve Bushing - Page 2 of 2



_										
וו	0	m	ш	м	2	iza	31	^	n	

No

Fiig:

A045a0

Mil-std (military Standard):

Mil-a-8625 spec.