# NSN 3120-00-881-1297

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-00-881-1297

#### **Overall Length:**

Between 0.2420 inches and 0.2570 inches

#### **Body Outside Diameter:**

Between 0.5631 inches and 0.5638 inches

## **Body Inside Diameter:**

Between 0.4375 inches and 0.4390 inches

#### Flange Outside Diameter:

Between 0.6770 inches and 0.6970 inches

#### Flange Width:

Between 0.0570 inches and 0.0620 inches

## Corner Shape:

Undercut left flange body corner

#### Surface Finish:

100.0 microinches intermediate layer

#### **Special Features:**

Id and od to be parallel and concentric within 0.0030 tir

## Material:

Steel comp 4130 or steel comp 8630

## **Material Specification:**

Mil-s-6758 military specification 1st material response or mil-s-6050 military specification 2nd material response

## Surface Treatment:

Cadmium

## Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

## Style Designator:

22c solid, external flange one end

## **Specification Data:**

80205-nas77 professional/industrial association standard

#### Shelf Life:

N/a

## Unit Of Measure:

```
--
```

# Demilitarization:

No

Fiig:

## A045a0

Mil-std (military Standard):

Mil-s-6758 spec.