NSN 3120-00-890-0763

Rod End Plain Bearing - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3120-00-890-0763

| Thread Class: |
|---|
| 3a |
| Thread Direction: |
| Right-hand |
| Shank Style: |
| Externally threaded |
| Overall Length: |
| 3.6330 inches |
| Bore Diameter: |
| Between 0.9995 inches and 1.0000 inches |
| Outer Member Outside Diameter: |
| 2.0800 inches |
| Bore Center To Shank End Distance: |
| 2.5930 inches |
| Outer Member Width: |
| Between 0.7920 inches and 0.8020 inches |
| Inner Member Width: |
| Between 0.9980 inches and 1.0000 inches |
| Shank Thread Length: |
| 1.4370 inches |
| Thread Diameter: |
| 1.000 inches |
| Thready Qty Per Inch (tpi): |
| 16 |
| Hardness Rating: |
| 38.0 rockwell c and 46.0 rockwell c |
| Special Features: |
| Threaded shank has a slot on the side 0.1610 in. W, 0.0150 in. Deep, 1.4370 in. Lg $$ |
| Material: |
| Steel comp xm-12 |
| Material Specification: |
| Ams 5659 assn standard single material response |
| Surface Treatment: |
| Chromium |
| Style Designator: |
| Ball type |
| Thread Series Designator: |
| Un |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

NSN 3120-00-890-0763

Rod End Plain Bearing - Page 2 of 2

Demilitarization:

No

Fiig:

A045a0

