NSN 3120-00-895-6386

Rod End Plain Bearing - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3120-00-895-6386

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Shank Style: |
| Externally threaded |
| Overall Length: |
| Between 1.9270 inches and 1.9470 inches |
| Bore Diameter: |
| Between 0.2495 inches and 0.2515 inches |
| Outer Member Outside Diameter: |
| Between 0.7400 inches and 0.7600 inches |
| Bore Center To Shank End Distance: |
| Between 1.5520 inches and 1.5720 inches |
| Outer Member Width: |
| Between 0.2760 inches and 0.2860 inches |
| Inner Member Width: |
| Between 0.3700 inches and 0.3750 inches |
| Shank Thread Length: |
| 1.0000 inches |
| Static Radial Load Rating: |
| 1550 pounds |
| Thread Diameter: |
| 0.250 inches |
| Thready Qty Per Inch (tpi): |
| 28 |
| Hardness Rating: |
| 60.0 rockwell c inner member |
| Material: |
| Steel rod end body |
| Material Specification: |
| Qq-b-637 comp 3 federal specification single material response race insert |
| Surface Treatment: |
| Cadmium rod end body |
| Style Designator: |
| Ball type |
| Thread Series Designator: |
| Unf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

NSN 3120-00-895-6386

Rod End Plain Bearing - Page 2 of 2

Demilitarization:

No

Fiig:

A045a0

