## NSN 3120-00-903-9513

Sleeve Bearing Half - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3120-00-903-9513

**Hole Diameter:** 

0.2600 inches second

**Overall Length:** 

Between 2.3580 inches and 2.3600 inches

**Body Outside Diameter:** 

Between 3.5015 inches and 3.5020 inches

**Body Inside Diameter:** 

Between 3.2526 inches and 3.2534 inches

**Lubrication Material:** 

Lubricating oil

Left Flange Outside Diameter:

Between 4.2920 inches and 4.3320 inches

**Right Flange Outside Diameter:** 

Between 4.2920 inches and 4.3320 inches

Left Flange Width:

Between 0.1310 inches and 0.1330 inches

**Right Flange Width:** 

Between 0.1310 inches and 0.1330 inches

Distance From Centerline Of Opening To Left End Of Bearing:

1.1800 inches second

**Lubricant Accommodation Style:** 

Grooved circular

**Locking Lug Height:** 

Between 0.0450 inches and 0.0550 inches

**Locking Lug Length:** 

Between 0.1900 inches and 0.2200 inches

**Locking Lug Width:** 

Between 0.2380 inches and 0.2430 inches

**Corner Shape:** 

Square right flange outside left corner

**Antirotation/lubrication Type And Quantity:** 

3 hole

**Surface Groove Location And Quantity:** 

1 internal

**Distance From Lug End To End Of Bearing:** 

Between 0.5310 inches and 0.5385 inches

Material:

Steel comp 1010 and steel comp 1015 outer layer

**Surface Treatment:** 

Tin

**Style Designator:** 

18d half sleeve, external flanges both ends

## NSN 3120-00-903-9513

Sleeve Bearing Half - Page 2 of 2



_			-		
C	hο	14		.ife	
•			_	.II C	-

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A045a0