

View Online at <https://aerobasegroup.com/nsn/3120-00-904-9057>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Shank Style:**

Externally threaded

**Overall Length:**

2.6875 inches

**Bore Diameter:**

Between 0.3745 inches and 0.3750 inches

**Outer Member Outside Diameter:**

1.1250 inches

**Bore Center To Shank End Distance:**

2.1250 inches

**Outer Member Width:**

Between 0.3500 inches and 0.3600 inches

**Inner Member Width:**

Between 0.8080 inches and 0.8130 inches

**Shank Thread Length:**

1.3750 inches

**Static Radial Load Rating:**

3540 pounds

**Thread Diameter:**

0.438 inches

**Thready Qty Per Inch (tpi):**

20

**Hardness Rating:**

55.0 rockwell c inner member and 62.0 rockwell c inner member

**Special Features:**

Nas559 standard keyway in shank

**Material:**

Steel comp 630 race insert

**Surface Treatment:**

Cadmium rod end body

**Style Designator:**

Ball type

**Test Data Document:**

81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A045a0