

View Online at <https://aerobasegroup.com/nsn/3120-00-904-9829>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Shank Style:**

Externally threaded

**Overall Length:**

Between 1.5530 inches and 1.5730 inches

**Bore Diameter:**

Between 0.1895 inches and 0.1915 inches

**Outer Member Outside Diameter:**

Between 0.6150 inches and 0.6350 inches

**Bore Center To Shank End Distance:**

Between 1.2400 inches and 1.2600 inches

**Outer Member Width:**

Between 0.2450 inches and 0.2550 inches

**Inner Member Width:**

Between 0.3070 inches and 0.3120 inches

**Shank Thread Length:**

0.7500 inches

**Static Radial Load Rating:**

865 pounds

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Hardness Rating:**

60.0 rockwell c inner member

**Special Features:**

6 1/2 degrees self-alignment in either direction, magnetic particle inspected<magnafluxed>rod end shank stamped w/letter<<m>>

**Material:**

Steel rod end body

**Material Specification:**

Qq-s-633 federal specification single material response rod end body

**Surface Treatment:**

Cadmium rod end body

**Surface Treatment Specification:**

Qq-p-416 federal specification single treatment response rod end body

**Style Designator:**

Ball type

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A045a0