## NSN 3120-00-905-7232

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-00-905-7232
Overall Length:
Between 0.6120 inches and 0.6270 inches
Body Outside Diameter:
Between 0.6257 inches and 0.6265 inches
Body Inside Diameter:
Between 0.5000 inches and 0.5015 inches
Flange Outside Diameter:
Between 0.7400 inches and 0.7600 inches
Flange Width:
Between 0.0570 inches and 0.0620 inches
Corner Shape:
Undercut left flange body corner
Surface Finish:
100.0 microinches intermediate layer
Material:
Steel comp 4130
Material Specification:
Mil-s-6758 military specification single material response
-
Mil-s-6758 military specification single material response
Mil-s-6758 military specification single material response  Surface Treatment:
Mil-s-6758 military specification single material response  Surface Treatment:  Cadmium
Mil-s-6758 military specification single material response  Surface Treatment:  Cadmium  Surface Treatment Specification:
Mil-s-6758 military specification single material response  Surface Treatment:  Cadmium  Surface Treatment Specification:  Qq-p-416, type 2, cl 3 federal specification single treatment response
Mil-s-6758 military specification single material response  Surface Treatment:  Cadmium  Surface Treatment Specification:  Qq-p-416, type 2, cl 3 federal specification single treatment response  Style Designator:
Mil-s-6758 military specification single material response  Surface Treatment:  Cadmium  Surface Treatment Specification:  Qq-p-416, type 2, cl 3 federal specification single treatment response  Style Designator:  22c solid, external flange one end
Mil-s-6758 military specification single material response  Surface Treatment:  Cadmium  Surface Treatment Specification:  Qq-p-416, type 2, cl 3 federal specification single treatment response  Style Designator:  22c solid, external flange one end  Specification Data:
Mil-s-6758 military specification single material response  Surface Treatment:  Cadmium  Surface Treatment Specification:  Qq-p-416, type 2, cl 3 federal specification single treatment response  Style Designator:  22c solid, external flange one end  Specification Data:  80205-nas77 professional/industrial association standard
Mil-s-6758 military specification single material response  Surface Treatment:  Cadmium  Surface Treatment Specification:  Qq-p-416, type 2, cl 3 federal specification single treatment response  Style Designator:  22c solid, external flange one end  Specification Data:  80205-nas77 professional/industrial association standard  Shelf Life:
Mil-s-6758 military specification single material response  Surface Treatment:  Cadmium  Surface Treatment Specification:  Qq-p-416, type 2, cl 3 federal specification single treatment response  Style Designator:  22c solid, external flange one end  Specification Data:  80205-nas77 professional/industrial association standard  Shelf Life:  N/a
Mil-s-6758 military specification single material response  Surface Treatment:  Cadmium  Surface Treatment Specification:  Qq-p-416, type 2, cl 3 federal specification single treatment response  Style Designator:  22c solid, external flange one end  Specification Data:  80205-nas77 professional/industrial association standard  Shelf Life:  N/a
Mil-s-6758 military specification single material response  Surface Treatment:  Cadmium  Surface Treatment Specification:  Qq-p-416, type 2, cl 3 federal specification single treatment response  Style Designator:  22c solid, external flange one end  Specification Data:  80205-nas77 professional/industrial association standard  Shelf Life:  N/a  Unit Of Measure:
Mil-s-6758 military specification single material response  Surface Treatment:  Cadmium  Surface Treatment Specification:  Qq-p-416, type 2, cl 3 federal specification single treatment response  Style Designator:  22c solid, external flange one end  Specification Data:  80205-nas77 professional/industrial association standard  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:

Mil-std (military Standard):

Mil-s-6758 spec.