

View Online at <https://aerobasegroup.com/nsn/3120-00-913-6609>

Thread Class:

3a

Thread Direction:

Left-hand

Shank Style:

Externally threaded

Overall Length:

5.0500 inches

Bore Diameter:

Between 0.6245 inches and 0.6250 inches

Lubrication Material:

Lubricant, dry film

Outer Member Outside Diameter:

Between 1.5900 inches and 1.6100 inches

Bore Center To Shank End Distance:

Between 4.2400 inches and 4.2600 inches

Outer Member Width:

Between 0.5050 inches and 0.5150 inches

Inner Member Width:

Between 0.6200 inches and 0.6250 inches

Shank Thread Length:

1.8800 inches

Static Radial Load Rating:

19400 pounds

Thread Diameter:

0.875 inches

Features Provided:

Flush lubrication fitting

Thready Qty Per Inch (tpi):

14

Hardness Rating:

55.0 rockwell c inner member

Lubrication Feature:

Groove internal inner member and perforation internal inner member

Special Features:

Groove in shank 0.1560 in. Min 0.1610 in. Maximum wide by 0.0930 in. Min 0.1030 in. Maximum deep in thd lg, misalign 9.0 deg, shank offset to 60.0 degrees angle

Material:

Steel comp 630 race insert

Surface Treatment:

Cadmium rod end body

Style Designator:

Ball type

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0