

View Online at <https://aerobasegroup.com/nsn/3120-00-914-7609>

Thread Class:

3a

Thread Direction:

Right-hand

Shank Style:

Externally threaded

Overall Length:

Between 1.8000 inches and 1.8200 inches

Bore Diameter:

Between 0.2500 inches and 0.2505 inches

Outer Member Outside Diameter:

Between 0.7400 inches and 0.7600 inches

Bore Center To Shank End Distance:

Between 1.4200 inches and 1.4400 inches

Outer Member Width:

Between 0.2760 inches and 0.2860 inches

Inner Member Width:

Between 0.3700 inches and 0.3750 inches

Shank Thread Length:

Between 0.8500 inches and 0.9300 inches

Static Radial Load Rating:

4000 pounds

Thread Diameter:

0.313 inches

Features Provided:

Flush lubrication fitting

Thready Qty Per Inch (tpi):

24

Hardness Rating:

60.0 rockwell c inner member

Lubrication Feature:

Groove internal outer member

Material:

Steel comp e52100 inner member

Material Specification:

Ams 7440 assn standard single material response inner member

Surface Treatment:

Cadmium rod end body

Style Designator:

Ball type

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0