NSN 3120-00-916-6548

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-00-916-6548

Overall Length:

Between 0.6920 inches and 0.7070 inches

Body Outside Diameter:

Between 0.8132 inches and 0.8142 inches

Body Inside Diameter:

Between 0.6250 inches and 0.6265 inches

Flange Outside Diameter:

Between 0.9900 inches and 1.0100 inches

Flange Width:

Between 0.0570 inches and 0.0620 inches

Corner Shape:

Undercut left flange body corner

Surface Finish:

100.0 microinches intermediate layer

Special Features:

Id and od to be parallel and concentric within 0.0030 tir

Material:

Steel comp 4130 or steel comp 8630

Material Specification:

Mil-s-6798 military specification 1st material response or mil-s-6050 military specification 2nd material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Style Designator:

Solid, external flange one end

Specification Data:

80205-nas77 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

```
--
```

Demilitarization:

No

Fiig:

A045a0

Mil-std (military Standard):

Mil-s-6798 spec.