NSN 3120-00-922-1460

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-00-922-1460

| view Offilite at https://aerobasegroup.com/hist//3120-00-322-1400 |
|---|
| Overall Length: |
| Between 0.1520 inches and 0.1630 inches |
| Body Outside Diameter: |
| Between 0.3090 inches and 0.3100 inches |
| Body Inside Diameter: |
| Between 0.1900 inches and 0.1910 inches |
| Flange Outside Diameter: |
| 0.4380 inches |
| Flange Width: |
| Between 0.0420 inches and 0.0470 inches |
| Corner Shape: |
| Square outside right corner |
| Hardness Rating: |
| 39.0 rockwell c and 42.0 rockwell c |
| Surface Finish: |
| 125.0 microinches intermediate layer |
| Special Features: |
| Dimensions except id to be met before plating |
| Material: |
| Steel comp 4340 |
| Surface Treatment: |
| Cadmium and chromate |
| Surface Treatment Specification: |
| Mil-c-8837 military specification single treatment response |
| Style Designator: |
| 22c solid, external flange one end |
| Test Data Document: |
| 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A045a0 |

Mil-c-8837 spec.

Mil-std (military Standard):