NSN 3120-00-922-1479

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-00-922-1479

| view Offilite at https://aerobasegroup.com/hist//3120-00-322-1473 |
|---|
| Overall Length: |
| Between 0.1760 inches and 0.1890 inches |
| Body Outside Diameter: |
| Between 0.5003 inches and 0.5013 inches |
| Body Inside Diameter: |
| Between 0.3660 inches and 0.3680 inches |
| Flange Outside Diameter: |
| 0.6250 inches |
| Flange Width: |
| Between 0.0610 inches and 0.0640 inches |
| Corner Shape: |
| Square outside right corner |
| Hardness Rating: |
| 39.0 rockwell c and 42.0 rockwell c |
| Surface Finish: |
| 125.0 microinches intermediate layer |
| Material: |
| Steel comp 4340 or steel comp e4340 |
| Material Specification: |
| Mil-s-5000 military specification single material response |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Qq-p-416, type 2, cl 1 federal specification single treatment response |
| Style Designator: |
| 22c solid, external flange one end |
| Test Data Document: |
| 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A045a0 |

Mil-std (military Standard): Mil-s-5000 spec.